

Home Work PHY 554

HW 1 (10 points): Let us calculate the synchrotron radiation related problem in NSLS II. NSLS II adopts DBA lattice (separate function magnets). Here are the parameters:

Table 1: NSLS II parameters

Parameter	Value
Energy [GeV]	3.0
Circumference [m]	780
Number of dipoles	60
Dipole field [T]	0.4
Beam current [A]	0.5
RF frequency [MHz]	499.68
Harmonic number	1320

From the design parameters, we can calculate the following parameters:

Note: In DBA lattice, dispersion D and dispersion slope D' are zero at one end of dipoles and non-zero at the other end of the dipole. Find dispersion function inside the dipole magnet.

- What is the compaction factor α_c of the ring?
- What the energy loss per turn due to synchrotron radiation in the dipoles
- For accelerating phase $\pi/6$ in the RF cavity, what is minimum RF voltage is required?

How much is the power needed to compensate losses of the beam energy for synchrotron radiation? (neglect RF losses in the cavity – it is super-conducting)

- For actual RF voltage of 3MV, find the longitudinal tune of NSLS II ring
- Find the partition number \bar{D} due to synchrotron radiation in dipole.
- Find the longitudinal damping rate α_E and compare with the period of synchrotron oscillations.
- Find the equilibrium energy spread of NSLS II.

Hint: all dipoles in NSLS II are identical with uniform field ($\partial B_y / \partial x = 0$). First, find what is the length of the dipole. Calculate the dispersion in the dipole starting from $D=0$ and $D'=0$, and calculate all other integrals for this dipole. The rest – just multiply them by number of dipoles and use formulae from the lectures 14-15.