

Homework 19. Due November 18

Problem 1. 20 points. 1D emittance

For an ensemble or a distribution function of particles 1D geometrical emittance is defined as

$$\varepsilon_y^2 = \langle y^2 \rangle \langle y'^2 \rangle - \langle yy' \rangle^2;$$

$$\langle g(y, y') \rangle = \frac{\sum_{n=1}^{N_p} g(y_n, y'_n)}{N_p} = \int f(y, y') g(y, y') dy dy';$$

1. Show that the emittance is invariant to a Canonical linear (symplectic matrix) transformation of

$$\begin{bmatrix} y \\ y' \end{bmatrix} = M \begin{bmatrix} y \\ y' \end{bmatrix}$$

Note: use the fact that $\varepsilon_y^2 = \det \Sigma$; $\Sigma = \begin{bmatrix} \langle y^2 \rangle & \langle yy' \rangle \\ \langle yy' \rangle & \langle y'^2 \rangle \end{bmatrix}$; and find transformation rule for

the Σ matrix.

2. For one-dimensional betatron (y) distribution find components of eigen vector \mathbf{w}_y and \mathbf{w}'_y generating a given (positively defined)

$$\Sigma = \begin{bmatrix} \langle y^2 \rangle & \langle yy' \rangle \\ \langle yy' \rangle & \langle y'^2 \rangle \end{bmatrix};$$

This operation is called matching the beam into the beam-line optics.

Solution.

Problem 1. (1) Let's prove that

$$\begin{bmatrix} \tilde{y} \\ \tilde{y}' \end{bmatrix} = \begin{bmatrix} \tilde{X}_1 \\ \tilde{X}_2 \end{bmatrix} = M \begin{bmatrix} y \\ y' \end{bmatrix} = M \begin{bmatrix} X_1 \\ X_2 \end{bmatrix} \rightarrow \tilde{\Sigma} = M^T \Sigma M$$

by observing that

$$\Sigma_{ij} = \langle X_i X_j \rangle;$$

$$\tilde{\Sigma}_{ij} = \tilde{\Sigma}_{ji} = \langle \tilde{X}_i \tilde{X}_j \rangle = \langle M_{ik} X_k X_n M_{nj} \rangle =$$

$$= M_{ik} \langle X_k X_n \rangle M_{nj} = M_{ik} \Sigma_{ij} M_{nj}$$

(where we use the fact that one can extract constants from the averaging brackets) which in matrix form is equivalent to

$$\tilde{\Sigma} = M^T \Sigma M$$

The rest is easy since $\det M = 1$:

$$\det \tilde{\Sigma} = \det M^T \det \Sigma \det M = \det \Sigma$$

(2) Let's remember that

$$y = aw_y \cos\psi_y; \quad y' = a \left(w'_y \cos\psi_y - \frac{1}{w_y} \sin\psi_y \right)$$

and calculate averages using randomness of particles' phases

$$\langle \cos^2 \psi_y \rangle = \frac{1}{2}; \quad \langle \cos \psi_y \sin \psi_y \rangle = 0; \quad \langle \sin^2 \psi_y \rangle = \frac{1}{2}; \quad \frac{\langle a^2 \rangle}{2} = \epsilon_y$$

$$\langle y^2 \rangle = \langle a^2 w_y^2 \cos^2 \psi_y \rangle = w_y^2 \frac{\langle a^2 \rangle}{2} = \beta_y \frac{\langle a^2 \rangle}{2};$$

$$\langle yy' \rangle = \left\langle a^2 w_y \cos \psi_y \left(w'_y \cos \psi_y - \frac{1}{w_y} \sin \psi_y \right) \right\rangle = w_y w'_y \frac{\langle a^2 \rangle}{2} = -\alpha_y \frac{\langle a^2 \rangle}{2};$$

$$\langle y'^2 \rangle = \left\langle a^2 \left(w'_y \cos \psi_y - \frac{1}{w_y} \sin \psi_y \right)^2 \right\rangle = \frac{1 + (w'_y w_y)^2}{w_y^2} \frac{\langle a^2 \rangle}{2} = \frac{1 + \alpha_y^2}{\beta_y}.$$

$$\Sigma = \begin{bmatrix} \langle y^2 \rangle & \langle yy' \rangle \\ \langle yy' \rangle & \langle y'^2 \rangle \end{bmatrix} = \epsilon_y \begin{bmatrix} \beta_y & -\alpha_y \\ -\alpha_y & \frac{1 + \alpha_y^2}{\beta_y} \end{bmatrix}.$$

Thus, for 1D case it one can use this relation to design matched lattice for a given Σ matrix of the beam – for example at injection point into a storage ring. This matching minimizes RMS amplitudes of particles oscillation in the storage ring.